



HPX HARMONIE

THE SIMPLICITY ASSOCIATED WITH THE BEST VALUE FOR MONEY ON THE MARKET

2 YEAR WARRANTY


Parts and labor returned to the workshop
Optional extension

5 YEAR WARRANTY*

Compressor

2 YEAR WARRANTY*

Exchanger



ACCESSORIES INCLUDED

2x DN50 fittings
Anti-vibration supports
Winter cover

OPTIONAL ACCESSORY

Support Footbloc

* excluding frost

THE + PRODUCT



ABS LIFEPROOF BLACK

No corrosion, Antishock and UV resistant



HELIX TITANIUM EXCHANGER

High performance exchanger



INTEGRATED FLOW SENSOR

For automatic operation and integrated safety



LCD SCREEN

Complete LCD screen with error code reporting



HEATING/COOLING

Heat or cool-only operation with automatic mode



AUTO DEFROST

Automatic defrost by cycle inversion



**FOR POOLS
FROM 30 TO 70 M3**

**TECHNICAL
BENEFITS**

Our Harmonie is our simple and economical swimming pool heat pump, offering the best value for money. With its intuitive LCD screen, its use is a breeze. Thanks the environmentally friendly R32 gas and its filtration pump control, you benefit from maximum efficiency without compromise. Choose simplicity and accessibility with our heat pump model, designed to meet all your pool heating needs with ease.

**HPX
HARMONIE**

	HPX65 VIP02002	HPX85 VIP02004	HPX100 VIP02006	HPX120 VIP02008
Pool size M3*	30 - 40 m ³	40 - 50 m ³	50 - 60 m ³	60 - 70 m ³
MEASUREMENT CONDITIONS AIR 24°C / WATER 26/28°C				
Heating capacity kW	6,60	8,50	10,90	12,50
Power consumption kW	11,19	1,30	1,72	2,17
COP	5,60	6,50	6,30	5,80
MEASUREMENT CONDITIONS AIR 15°C / WATER 26/28°C				
Heating capacity kW	5,60	7	8,40	10,30
Power consumption kW	1,14	1,28	1,70	2,10
COP	4,90	5,50	5	4,90
MEASUREMENT CONDITIONS AIR 35°C / WATER 27°C				
Cooling capacity kW	3,90	4,80	6,10	6,80
Power consumption kW	1,37	1,48	1,97	2,56
EER	2,90	3,30	3,10	2,70
FURTHER INFORMATION				
Noise level at 1m dB(A)	50	50	55	55
Operating temperature °C	5 to 43			
Gas / Weight Kg	R32/0,5	R32/0,71	R32/0,75	R32/0,95
Recommended water flow m3/h	2 - 4	2 - 4	2 - 4	2 - 4
Hydraulic connection mm	50			
Electrical connection	230V/1Ph/50Hz			
Max current A	6,80	7,60	10,20	13
Air discharge direction	Horizontal			
Dimensions (LxWxH) mm	830x340x555	980x455x585	980x455x585	1055x465x650
Net weight Kg	41	51	53	60

* Pool size recommended for a pool with a protective cover and favorable climate